

# PSUB 120T

## Ceiling subwoofer - 120 W



EN 54 24

- This 120W powered subwoofer is equipped with a 200mm high-performance system featuring 4 power adjustments 120/60/30/15W.
- PSUB 120T offers an amazing deep bass response which gives your voice alarm installation a rich sound quality.
- Power tapings are easily set at the front of the speaker, a low impedance operation at 4ohm is also possible. The crossover frequency is set to 135Hz. You can change the phase 180° by a switch at the front. To make things perfect the metal housing in RAL 9016 guarantees long-term durability.
- Protection class IP21C secures the speaker against the risks of environmental influences. The speaker chassis is impregnated against wetness. Easy installation via screw mounting system. Perfectly suitable for installations where high sound quality is demanded.



| Model                 | PSUB 120T                  |
|-----------------------|----------------------------|
| Body & grill          | ABS / Metal                |
| Nominal power         | 120W                       |
| Nominal Impedance     | 83Ω                        |
| Power 100V Line       | 120 / 60 / 30 / 15W        |
| Impedance             | 83 / 167 / 333 / 667Ω - 4Ω |
| Bandwidth             | 32 - 280Hz                 |
| Sensitivity (1W/1m)   | 87dB                       |
| SPL MAX 1m            | 107,8dB                    |
| Dimensions (mm)       | Ø 319 x P 250              |
| Ceiling Cut-out       | Ø 302mm                    |
| Weight                | 6,4kg                      |
| Operating temperature | -10°C ~+55°C               |
| Protection Index      | IP21C                      |
| Color                 | RAL 9016                   |

Bandwidth

